

# SAFETY DATA SHEET

#### Section 1. Identification of the material and the supplier

Product: **Deep Pour Liquid Glass Casting Resin (Base)** 

Product Use: Epoxy resin hardening agent

Restriction of Use: Refer to Section 15

Australian Supplier: **Norglass Paints** Address: 59 Moxon Road

Punchbowl NSW 2196

Australia

+61 2 9708 2200 Telephone: Email: info@norglass.com.au

New Zealand Supplier: XXX Address: XXX XXX

Telephone: 0508 724687

**Emergency Numbers:** 

Australia: 13 1126 (Poisons Information Centre) **New Zealand:** 0800 764 766 (National Poison Centre)

Date of SDS Preparation: 30 April 2021

#### Section 2. **Hazards Identification**

#### Australia:

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

### **New Zealand:**

This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2020

EPA Approval No: Surface Coatings and Colourants (subsidiary) - HSR002670

#### **Pictograms**





Irritant

**Ecotoxic** 

Signal Word: Warning

GHS Classification and Category   Hazard Code   Hazard Statement		Hazard Statement
Skin irritation Cat. 2	H315	Causes skin irritation.
Eye irritation Cat. 2	H319	Causes serious eye irritation.
Skin sensitisation Cat. 1	H317	May cause an allergic skin reaction.

Product Name: Deep Pour Liquid Glass Casting Resin SDS Prepared by: Technical Compliance Consultants (NZ) Ltd

Date of SDS: 30 April 2021 Tel: 64 9 475 5240 www.techcomp.co.nz

Hazardous to the aquatic	H411	Toxic to aquatic life with long lasting
environment chronic Cat. 2	П411	effects.

<b>Prevention Code</b>	Prevention Statement
P102	Keep out of reach of children.
P103	Read label before use.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective clothing as detailed in Section 8.

Response Code	Response Statement
P362	Take off contaminated clothing and wash before re-use.
P391	Collect spillage.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P305 +	IF IN EYES: Rinse cautiously with water for several minutes. Remove
P351+P338	contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.

Storage Code	Storage Statement
None allocated	

Disposal Code	Disposal Statement
P501	Dispose of according to Local Regulations or Authorities

# Section 3. Composition / Information on Ingredients

Ingredients	Wt%	CAS NUMBER.
bis[4-(2,3- epoxypropoxy)phenyl]propane	60 - 100	1675-54-3
oxirane, mono[(C12-14- alkyloxy)methyl] derivs	10 - <25	68609-97-2

Section 4	First Aid	Measures
Jeculon 7	I II St AIU	ricasules

## Routes of Exposure:

If in Eyes Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. If eye irritation persists: Get medical

advice/attention.

If on Skin Take off contaminated clothing and wash before re-use. Wash skin with

plenty of soap and water. If skin irritation or rash occurs: Get medical

advice/attention.

If Swallowed Rinse out mouth and then drink plenty of water. Seek medical advice if

needed.

If Inhaled Remove person to fresh air. Remove contaminated clothing and loosen

remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Get medical advice if

breathing becomes difficult or if you feel unwell.

# Most important symptoms and effects, both acute and delayed

Symptoms:

**Ingestion:** Not applicable. **Inhalation:** Not applicable.

**Skin:** Causes skin irritation. May cause an allergic skin irritation.

Product Name: Deep Pour Liquid Glass Casting Resin SDS Prepared by: Technical Compliance Consultants (NZ) Ltd

Date of SDS: 30 April 2021 Tel: 64 9 475 5240 www.techcomp.co.nz

**Eves:** Causes severe eye irritation.

**Chronic:** Not applicable.

Section 5.	Fire Fighting Measures	
------------	------------------------	--

Hazard Type	Non Flammable
Hazards from combustion products	No further relevant information available.
Suitable Extinguishing media	CO2, extinguishing powder or water jet. Fight larger fires with water spray.
Precautions for firefighters and special protective clothing	Wear self-contained respiratory protective device. Wear fully protective suit. Dispose of fire debris and contaminated firefighting water in accordance with official regulations. Collect contaminated firefighting water separately. It must not enter the sewage system.
HAZCHEM CODE	3Z

### Section 6. Accidental Release Measures

### **Personal precautions:**

Wear protective equipment as detailed in Section 8. Clear area of any unprotected personnel.

### **Environmental precautions:**

Do not allow product to reach sewage system or water bodies.

Do not allow to enter the ground/soil.

# **Spill and Disposal procedures:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of contaminated material as waste according to Section 13.

# Section 7. Handling and Storage

# **Precautions for Handling:**

- Read label before use.
- Wash hands thoroughly after handling.
- Contaminated work clothing should not be allowed out of the workplace.
- Ensure good ventilation/exhaustion at the workplace.
- Avoid release to the environment.
- Wear protective clothing as detailed in Section 8.

### **Precautions for Storage:**

- Store away from incompatible materials listed in Section 10.
- Prevent any seepage into the ground.
- Keep out of reach of children.

## Section 8 Exposure Controls / Personal Protection

# **WORKPLACE EXPOSURE STANDARDS (provided for guidance only)**

TWA STEL Substance ppm mg/m³ ppm mg/m³

No ingredients have exposure limits

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices NOV 2019 11TH EDITION.

Product Name: Deep Pour Liquid Glass Casting Resin SDS Prepared by: Technical Compliance Consultants (NZ) Ltd

Date of SDS: 30 April 2021 Tel: 64 9 475 5240 www.techcomp.co.nz

· DNELs			
1675-54-3 bis[4-(2,3-epoxypropoxy)phenyl]propane			
Dermal	DNEL worker	0.75 mg/kg bw/day (Long term - systemic effects)	
Inhalative	DNEL worker	4.93 mg/m <sup>3</sup> (Long term - systemic effects)	
• PNECs			
1675-54-3 bis[4-(2,3-	epoxypropoxy)pheny	yl]propane	
PNEC aqua		0.006 mg/L (fresh water)	
		0.001 mg/L (marine water)	
PNEC sediment		0.341 mg/kg sediment (fresh water)	
		0.034 mg/kg sediment (marine water)	
PNEC STP		10 mg/l (sewage)	
PNEC soil		0.065 mg/kg soil dw (soil)	
PNEC oral		11 mg/kg food (secondary poisoning)	

# **Engineering Controls**

No data available.

# **Personal Protection Equipment**



Eyes	Tightly sealed safety glasses with side shields.
Hands	The glove material has to be impermeable and resistant to the product/ the
	substance/ the preparation.
	Material of gloves
	Nitrile rubber, NBR
	Butyl rubber, BR
	Recommended thickness of the material: ≥ 0.4 mm
Skin	Protective work clothing.
Respiratory	Not required.
General	Keep away from foodstuffs, beverages and feed. Immediately remove all
	soiled and contaminated clothing. Wash hands before breaks and at the end
	of work. Avoid contact with the eyes and skin.

Section 9 Physical and Chemical Properties	
--	--

Appearance	Light yellow fluid
Odour	Characteristic
Odour Threshold	Not applicable
pH	11.6
<b>Boiling Point</b>	201°C
Solidification point	-8°C
Melting Point	Not available
Freezing Point	Not applicable
Flash Point	140 °C
Flammability	Not applicable
Upper and Lower	Product does not present an explosion hazard.
<b>Exposure Limits</b>	
<b>Volatile Component</b>	Not available
Vapour Pressure @ 20°C	<2 hPa
Density at 20°C	1.14 g/cm <sup>3</sup>
Solubility in /	Not miscible or difficult to mix.
Miscibility with Water:	
Partition Coefficient:	Not applicable
Auto-ignition	Product is not selfigniting.

Product Name: Deep Pour Liquid Glass Casting Resin Date of SDS: 30 April 2021 SDS Prepared by: Technical Compliance Consultants (NZ) Ltd Tel: 64 9 475 5240 www.techcomp.co.nz

Temperature	
Ignition Temperature	>200 °C
Decomposition	Not applicable
Temperature	
Viscosity Dynamix @	1 -1.3 Pas
20°C	
<b>Particle Characteristics</b>	Not applicable

# **Section 10. Stability and Reactivity**

Stability of Substance	This product is stable under normal conditions.	
Possibility of hazardous	Exothermic polymerisation. May produce violent reactions with	
reactions	bases and numerous organic substances including alcohols and	
	amines.	
Conditions to Avoid	No further relevant information available	
<b>Incompatible Materials</b>	No further relevant information available	
<b>Hazardous Decomposition</b>	No decomposition if used according to specifications.	
Products		

# Section 11 Toxicological Information

### **Acute Effects:**

Swallowed	Not applicable.	
Dermal	Not applicable.	
Inhalation	Not applicable.	
Eye	ye Causes severe eye irritation.	
Skin	Causes skin irritation. May cause an allergic skin reaction.	

## **Chronic Effects:**

Carcinogenicity	Not applicable
Reproductive	Not applicable
Toxicity	
Germ Cell	Not applicable
Mutagenicity	
Aspiration	Not applicable
STOT/SE	Not applicable
STOT/RE	Not applicable

bis[4-(2,3-epoxypropoxy)phenyl]propane (6175-54-3)	
LD50 oral rat	15000 mg/kg (Rat)
LD50 dermal rabbit	23000 mg/kg (Rabbit)

# Section 12. Ecotoxicological Information

GHS Classification: Hazardous to the aquatic environment chronic Cat. 2 = Toxic to aquatic life with long lasting effects.

bis[4-(2,3-epoxypropoxy)phenyl]propane (6175-54-3)	
Fish Toxicity	2 mg/l (Oncorhynchus mykiss) (LC50(96h))
Daphnia Toxicity	1.8 mg/l (daphnia magna) (EC50(48h))
Algae Toxicity	11 mg/l (algae) (EC50(72h))

Persistence and degradability	The product is not easily biodegradable.	
Bioaccumulation	No data available	
Mobility in Soil	No data available	
Other adverse effects	No data available	
Precautions	Toxic for aquatic organisms	
	Water hazard class 2 (German Regulation) (Self-	

Product Name: Deep Pour Liquid Glass Casting Resin SDS Prepared by: Technical Compliance Consultants (NZ) Ltd

Date of SDS: 30 April 2021 Tel: 64 9 475 5240 www.techcomp.co.nz

assessment): hazardous for water

Do not allow product to reach ground water, water course
or sewage system. Danger to drinking water if even small
quantities leak into the ground.

### Section 13. Disposal Considerations

**Disposal Method:** Empty contaminated packaging thoroughly. They may be recycled after thorough and proper cleaning.

**Disposal methods to avoid:** Do not allow to enter waterways.

# Section 14 Transport Information

This product is classified as a Dangerous Good for transport in NZ; NZS 5433:2012 and Australian Dangerous Goods Code ADG7 and NOHSC:1008(2004)



Road and Rail Transport

UN No: 3082 Class-primary 9 Packing Group III

Proper Shipping Name: HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis[4-(2,3-

epoxypropoxy)phenyl]propane)

Air Transport

UN No: 3082
Class-primary 9
Packing Group III

Proper Shipping Name: HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis[4-(2,3-

epoxypropoxy)phenyl]propane)

Marine Transport

UN No: 3082
Class-primary 9
Packing Group III
Marine Pollutant Yes

Proper Shipping Name: HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (bis[4-(2,3-

epoxypropoxy)phenyl]propane)

### **Limited Quantities Statement:**

If the product's individual container is below 5L, it can be transported as a non-DG as long as the product packaging is still labelled as per DG requirements and the driver is given safety information in accordance with Chapter 3.4 of the UNRTDG.

### Section 15 Regulatory Information

### Australia:

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.

Classified as a **Schedule 5** Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

#### **New Zealand:**

This substance is classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2020

Product Name: Deep Pour Liquid Glass Casting Resin
Date of SDS: 30 April 2021

SDS Prepared by: Technical Compliance Consultants (NZ) Ltd
Tel: 64 9 475 5240 www.techcomp.co.nz

HSW (HS) Regulations 2017 and EPA Notices	Trigger Quantity
Certified Handler	Not required
Location Certificate	Not required
Tracking Trigger Quantities	Not required
Signage Trigger Quantities	1000L (Hazardous to the aquatic
	environment chronic Cat. 2)
Emergency Response Plan	1000L (Hazardous to the aquatic
	environment chronic Cat. 2)
Secondary Containment	1000L (Hazardous to the aquatic
	environment chronic Cat. 2)
Restriction of Use	Only use for the intended purpose.

Section 16 Oth	er Information
Glossary	
Cat	Category
EC <sub>50</sub>	Median effective concentration.
EEL	Environmental Exposure Limit.
EPA	Environmental Protection Authority
HSNO	Hazardous Substances and New Organisms.
HSW	Health and Safety at Work.
LC <sub>50</sub>	Lethal concentration that will kill 50% of the test organisms
	inhaling or ingesting it.
LD <sub>50</sub>	Lethal dose to kill 50% of test animals/organisms.
LEL	Lower explosive level.
OSHA	American Occupational Safety and Health Administration.
TEL	Tolerable Exposure Limit.
TLV	Threshold Limit Value-an exposure limit set by responsible
	authority.
UEL	Upper Explosive Level
WES	Workplace Exposure Limit

### References:

# Australia:

- 1. Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.
- 2. National Industrial Chemicals Notification and Assessment Scheme (NICNAS).
- 3. Standard for the Uniform Scheduling of Medicines and Poisons.
- 4. Australian Code for the Transport of Dangerous Goods by Road & Rail.
- 5. Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.
- 6. Workplace exposure standards for airborne contaminants, Safe work Australia.
- 7. American Conference of Industrial Hygienists (ACGIH).
- 8. Globally Harmonised System of Classification and Labelling of chemicals.

#### New Zealand:

- 1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
- 2. Workplace Exposure Standards and Biological Exposure Indices Nov 2017 edition.
- 3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
- 4. Transport of Dangerous goods on land NZS 5433:2012
- 5. HSW (Hazardous Substances) Regulations 2017

#### Disclaimer

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage

Product Name: Deep Pour Liquid Glass Casting Resin
Date of SDS: 30 April 2021

SDS Prepared by: Technical Compliance Consultants (NZ) Ltd
Tel: 64 9 475 5240 www.techcomp.co.nz

(including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact the Australian Manufacturer or New Zealand distributor, if further information is required.

Issue Date: 30 April 2021 Review Date: 30 April 2026

Product Name: Deep Pour Liquid Glass Casting Resin SDS Prepared by: Technical Compliance Consultants (NZ) Ltd

Date of SDS: 30 April 2021 Tel: 64 9 475 5240 www.techcomp.co.nz