

Woodcare®

Wood Stain

Product Base Code: WIWS

	Product Description				
	<p>Haymes Paint Woodcare Wood Stain is a penetrating, oil-based stain designed to add vibrance and colour to interior timber and preserve its natural character. This easy-to-apply finish will enhance the grain of your timber and rejuvenate dull timber surfaces.</p>				
Key Features & Benefits					
 Interior use only	 Mineral Turpentine wash-up	 Coverage Up to 12 sqm/L	 Recoat 24 hrs	Enhances timber grain	Adds colour to transform your timber
				Simple to apply	Achieve a professional result
				Ready for use	Apply directly to the timber

Where to use	
Substrate :	Timber-Interior, Timber-Plywood and Timber-Veneer
Interior :	Built-in robes/Cupboards, Benchtops, Doors, Furniture, Panelling, Skirting and Architraves, Trims, Walls and Window Frames

Typical Properties	
Colour	Liming White, Cedar, Maple, Walnut, Teak, Baltic Pine, Blackwood, Ebony, Jarrah and Mahogany
Application method	Brush, cloth
Clean-up	Mineral Turpentine
Dry time - touch dry	8 hours
Dry time - recoat	24 hours
Sizes	250mL, 500mL, 1L
VOC	663 g/L
Volume solids	16%
Film build wet	83 µm
Film build dry	13 µm

Precautions

- Do NOT apply if ambient temperature is less than 10°C , greater than 35°C or if temperature will drop below 10°C during the drying period.
- All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperatures or higher humidity, drying times will be extended.
- Haymes Wood Stain is NOT suitable for use as a finish coat. You must apply a suitable Haymes clear finish after applying Wood Stain.
- Stain colour may vary depending on the natural timber colour. Prior to commencing an application, test the colour on an off-cut or in an inconspicuous area.
- To reduce the depth of colour, thin Wood Stain with mineral turpentine. If a deeper colour is required, apply additional coats.
- Once you have achieved your desired stain colour on your test area, apply a coat of your chosen clear coating to check that the finish meets your requirements.
- If more than one can of Haymes Woodcare_ Wood Stain is required, combine all cans in one clean metal or glass container and stir thoroughly with a broad, flat stirrer.
- Wear disposable or rubber gloves to avoid skin contact.
- Contaminated cloths may spontaneously combust. Spread contaminated cloths flat or soak in water immediately after use.
- Allow to dry in a cool, well-ventilated area before disposal.

Surface Preparation

General surface preparation	If required, fill nail holes, cracks and imperfections with Haymes Woodcare_ Wood Putty. Please ensure you have selected a Haymes Woodcare_ Wood Putty which closely matches your timber colour. Preparation is vital to ensuring a quality finish. Seek professional advice for preparing and sanding your floor before applying the floor coating.
Previously stained or clear coated surfaces	<ol style="list-style-type: none"> 1. Remove all previous stains and coating by stripping and/or sanding. 2. Ensure surface is clean, bare, dry and free of mould, wax, grease and other contaminants. 3. Follow application instructions.
New timber	<ol style="list-style-type: none"> 1. Ensure surface is clean, bare, dry and free of mould, wax, grease and other contaminants. 2. Sand timber with 240-grit sandpaper in the direction of the grain until smooth. Remove dust. 3. Follow application instructions.
IMPORTANT:	You must consult the installation guide of the construction product you are using for information on coatings and finishing guide to determine product suitability prior to commencing work. For further information and product specification consult a Haymes Paint representative on 1800 033 431.

Application

- Shake thoroughly before and during use.
- Apply first coat by brush or cloth. If applying by brush, apply evenly in the direction of the grain. If applying by cloth, apply in a circular motion. Apply adequate product to end grain and all edges.
- Allow to stand for two to three minutes.
- Wipe off the excess stain using a clean, lint-free cloth.
- If required, apply subsequent coats. Allow four hours dry time between coats.

Application

- To complete the project, apply Haymes Woodcare Interior Varnish after eight hours or Haymes Woodcare Aqualac Clear after 24 hours, following the relevant product application instructions.

Care and Maintenance

Protect the coating from abrasive contact for seven days. After seven days, the finish can be cleaned with a mild detergent and a soft cloth. Regularly inspect surfaces for signs of wear and tear. If the surface is wearing, immediately recoat timber with a suitable Haymes Woodcare clear coating.

Storage

Read the Safety Data Sheet (SDS) for this product for specific directions on storage (section 7 of the SDS) and transport (section 10 of the SDS). To obtain a copy of the SDS, go to the Haymes Paint website, <https://www.haymespaint.com.au/products/technical/product-data-sheets-and-safety-data-sheets/>, or contact Haymes Service Express on 1800 033 431. Containers must be secured and stored upright during transit. Protect from extremes of temperature. Store in a cool, dry, well-ventilated place and out of direct sunlight. Check regularly for leaks. Ensure the container label remains legible for future identification and usage.

Safety & First Aid

Read the Safety Data Sheet (SDS) for this product, prior to using this product. The SDS contains important information on how to use this product safely including hazards and precautions, personal protective equipment, storage and first aid in the event of an emergency. To obtain a copy of the SDS, go to the Haymes Paint website, <https://www.haymespaint.com.au/products/technical/product-data-sheets-and-safety-data-sheets/>, or contact Haymes Service Express on 1800 033 431.

If the product is swallowed, phone the Poisons Information Centre on 13 11 26 or contact a Doctor. Keep out of reach of children. Flammable liquid and vapour. Harmful if inhaled. May cause drowsiness or dizziness. Avoid breathing vapours. Only use this product in a well ventilated space and away from ignition sources. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using.

Protect our Environment

Do NOT pour any leftover product down the drain. Retain in a marked, sealed container for future use or disposal via chemical waste collection programs such as Paintback®. Visit www.paintback.com.au for details of your nearest depot. Dried empty containers can be recycled and should be disposed of via recycling facilities.

Manufacturer's comment

This product has been designed as part of an integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Important safety information is available on the Safety Data Sheet available from Haymes Paint website www.haymespaint.com.au. Further information about other Haymes products recommended to be used in conjunction with this product are available from the website in the form of Product Data Sheets in relation to those products. We are continually updating materials and methods, so please ensure you have the latest information on the Haymes Paint website.

Disclaimer

The information provided in this Product Data Sheet is correct at the time of preparation, but is subject to change. It is your responsibility to check the Haymes Paint website at www.haymespaint.com.au to ensure that you have the most current Product Data Sheet. Product application and performance is affected by environmental conditions at the time of application and drying. Paint applied in conditions outside of what is recommended may dry more slowly or be less durable, or produce a less uniform appearance.

Version

Version and Date Issued	Version 2.0 Date 10/08/2021
Supersedes	Version 1.0 Date 01/11/2016

Henry Haymes Pty Ltd
A.B.N. 14 004 201 638
Waringa Drive
Wendouree Industrial Park
Ballarat Vic 3355
Freecall 1800 033 431
www.haymespaint.com.au