

Ultra Premium

Prepcoat Ultracover

Product Base Code: UPUC

	Product Description	
	<p>Haymes Paint Ultracover is a low odour, water-based primer, sealer and undercoat. It delivers superior adhesion on a wide range of surfaces, including aged and gloss enamels. Suitable for interior and exterior use, Ultracover seals common household stains and can be top-coated with either water-based or oil-based paints while offering the convenience of water wash-up.</p>	
	Key Features & Benefits	
	Superior adhesion	No sanding required on most surfaces
	Stain sealer	Seals common household stains
	Universal	Use on a wide range of surfaces
	Easy to apply	Fantastic coverage and levelling

Where to use	
Substrate :	Aluminium Brick Concrete Cement Sheeting Masonry Plasterboard Colorbond® Zinc treated steel Timber Laminex® and MDF
Interior :	Built-in robes/Cupboards, Ceilings, Doors, Skirting and Architraves, Trims, Walls and Window Frames
Exterior :	Doors, Eaves, Facias, Gutters and Downpipes, Pergolas, Verandas, Trims, Walls and Window Frames
<p>Suitable for use over water or oil based paint. Seals stains such as permanent marker, pencil, water, smoke, tobacco, mildew and tannin stains.</p>	

Typical Properties	
Colour	White
Application method	Brush, roller, spray, airless spray
Clean-up	Water
Dry time - touch dry	20 minutes
Dry time - recoat	2 hours
Coverage	Up to 16 sqm/L dependent upon surface porosity, profile and method of application.
Sizes	500mL, 1L, 2L, 4L, 10L
VOC	<5 g/L
Volume solids	40%

Film build wet	63 µm
Film build dry	25 µm

Precautions

- Do NOT apply if the ambient temperature is less than 10°C or greater than 35°C or if conditions will drop below 10°C during the drying period. Under warmer conditions refer to thinning advice.
- All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity, drying times will be extended.
- Do NOT apply if rain or dew is expected within 24 hours of application.
- Provide adequate ventilation during application and the drying period.
- Do NOT paint in direct sunlight.
- Under normal conditions, the coating may require up to seven days curing to develop hardness and properties.
- The product can be tinted to Haymes Tinted Undercoat (TU) formulations only. Colours outside of the specified TU range can affect specified product performance.

Surface Preparation

General surface preparation	All surfaces must be clean, bare, dry and free of wax, grease and other surface contaminants. Fill any cracks, nail holes or imperfections with the appropriate filler. Sand smooth and dust down. If mould is present, treat the surface with a mould remover to effectively eliminate the mould spores. All traces of mould must be removed prior to painting.
Previously painted surface	Conduct an adhesion test [1], followed by a compatibility test [2]. Scrape all loose flaking paint. Sand surface smooth to a dull finish and remove all dust. Apply one coat of Haymes Paint Ultracover to any patched areas followed by one coat over the entire surface.
Timber	Apply directly to a correctly prepared surface. On tannin-rich timber and timbers prone to knot bleeding, apply one coat of Haymes Ultralock to the knot (spot prime) then a full coat of Ultralock over the entire timber surface. For pre-primed timbers, please refer to the manufacturer's painting specification [3].
Galvanised iron	Thoroughly degrease new surfaces with a non-metallic scourer. Wash degreased and weathered surfaces using Haymes Paint Unikleen sugar soap. Rinse with clean water. Apply one coat of Haymes Paint Ultracover. Structural Galvanised iron must be abraded and primed with a metal or etch primer.
Zincalume®	Remove oil using a solvent degreaser, then wash with Haymes Paint Unikleen using a mop or soft bristle brush, rinse with clean water. Apply one coat of Haymes Paint Ultracover.
Aluminium	Wash with Haymes Paint Unikleen & rinse with clean water. Abrade the surface with a non-metallic scourer. Apply one coat of Haymes Paint Ultracover.
MDF	Check that any pre primers are suitable for painting by cutting an X through the coating. Press tape firmly over the X and pull off sharply. If any coating is stuck to the tape, then the pre-primer must be entirely removed by sanding prior to any further painting. Sand smooth and remove all dust. Apply one coat of Haymes Ultraseal or Ultracover.

Surface Preparation	
Stain sealing	Wash the surface thoroughly to remove as much stain as possible and allow to dry. Apply Haymes Ultracover and allow to dry overnight prior to top coating. Some stains may require two (2) coats of Haymes Ultracover, and in the case of severe staining, it may be necessary to use Haymes Ultralock or UltraHold solvent-based primer sealer undercoat.
Colorbond®	Ensure weathered surfaces are clean and free of salts or other deposits. Wash new surfaces with a non-metallic scourer and Haymes Paint Unikleen sugar soap. Apply one coat of Haymes Paint Ultracover.
Laminex®	Wash with Haymes Unikleen and rinse with clean water. Sand surface with sandpaper to de-gloss surface. Apply one coat of Haymes Ultracover.
Brick, concrete, masonry	New concrete must be left to cure for 28 days before painting. Clean the surface using a pressure washer and allow to dry. Ensure concrete surfaces are free from any bond breakers, formwork release agents and efflorescence. Apply one coat of Haymes Paint Ultracover.
Zincanneal®, Galvanneal and Duragal®	Ensure Zinc treated surfaces are clean and free of oil, salts or other deposits. Remove oil using a solvent degreaser, then wash new surfaces with a non-metallic scourer and Haymes Paint Unikleen sugar soap. Apply one coat of Haymes Paint Ultracover.
Plasterboard	Surface must be free of dust and grease, apply directly to a correctly prepared surface.
Preprimed cement sheeting (Scyon Matrix)	Surface must be free of dust and grease, or other contaminants. Conduct an adhesion test [1]. Apply one coat of Haymes Ultracover.
Adhesion test	[1] To check the adhesion of an existing coating, cut an 'X' lightly into the coating and firmly apply adhesive tape across the cut and then remove tape. If the tape removes the existing coating, remove all previous coatings before painting.
Compatibility test	[2] Test for compatibility with a previous coating by sanding and cleaning a small inconspicuous area. Apply 1 coat of the desired topcoat and allow to dry. After 24 hours, conduct an adhesion test. If the tape removes the coating, remove all previous coatings before painting. It is recommended to conduct the compatibility test in several areas.
Preprimed timber	[3] Some primers used on preprimed timber are of low quality. Unless a painting specification is supplied by the timber manufacturer, the timber must be sanded back to bare timber before coating.
IMPORTANT:	You must consult the installation guide of the construction product you are using for information on coatings and finishing guide to determine product suitability prior to commencing work. For further information and product specification consult a Haymes Paint representative on 1800 033 431.

Application	
<ul style="list-style-type: none"> • Stir thoroughly before and during application using a broad flat stirrer. • Apply one coat. • Application methods: <ul style="list-style-type: none"> • Brush: Use a quality synthetic brush. • Roller: Smooth to semi-smooth surfaces use 11-12mm nap length. • Semi-smooth to rough surfaces use 14-18mm nap length. • Rough or uneven surfaces use 20-22mm nap length. 	

Application

- Spray: For airless spray use a 15-17 thou @ 2000-2500 psi.
- The use of low-pressure tips will require a lower pressure range.

Thinning

This product should not be thinned unless the surface is very porous or it is required for spraying. If necessary, use up to 100mL of clean water per litre of product.

Care and Maintenance

Protect the surface against knocks and abrasion for 7 days. Maximum adhesion may take several days to develop depending on film build and drying conditions.

Storage

Read the Safety Data Sheet (SDS) for this product for specific directions on storage (section 7 of the SDS) and transport (section 10 of the SDS). To obtain a copy of the SDS, go to the Haymes Paint website, <https://www.haymespaint.com.au/products/technical/product-data-sheets-and-safety-data-sheets/>, or contact Haymes Service Express on 1800 033 431. Containers must be secured and stored upright during transit. Protect from extremes of temperature. Store in a cool, dry, well-ventilated place and out of direct sunlight. Check regularly for leaks. Ensure the container label remains legible for future identification and usage.

Safety & First Aid

Read the Safety Data Sheet (SDS) for this product, prior to using this product. The SDS contains important information on how to use this product safely including hazards and precautions, personal protective equipment, storage and first aid in the event of an emergency. To obtain a copy of the SDS, go to the Haymes Paint website, <https://www.haymespaint.com.au/products/technical/product-data-sheets-and-safety-data-sheets/>, or contact Haymes Service Express on 1800 033 431.

If the product is swallowed, phone the Poisons Information Centre on 13 11 26 or contact a Doctor. Keep out of reach of children. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using.

Protect our Environment

Do NOT pour any leftover product down the drain. Retain in a marked, sealed container for future use or disposal via chemical waste collection programs such as Paintback®. Visit www.paintback.com.au for details of your nearest depot. Dried empty containers can be recycled and should be disposed of via recycling facilities.

Manufacturer's comment

This product has been designed as part of an integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Important safety information is available on the Safety Data Sheet available from Haymes Paint website www.haymespaint.com.au. Further information about other Haymes products recommended to be used in conjunction with this product are available from the website in the form of Product Data Sheets in relation to those products. We are continually updating materials and methods, so please ensure you have the latest information on the Haymes Paint website.

Disclaimer

The information provided in this Product Data Sheet is correct at the time of preparation, but is subject to change. It is your responsibility to check the Haymes Paint website at www.haymespaint.com.au to ensure that you have the most current Product Data Sheet. Product application and performance is affected by environmental conditions at the time of application and drying. Paint applied in conditions outside of what is recommended may dry more slowly or be less durable, or produce a less uniform appearance.

Version

Version and Date Issued	Version 2.0 Date 27/06/2022
Supersedes	Version 1 Date 13/07/2021

Henry Haymes Pty Ltd
A.B.N. 14 004 201 638
Waringa Drive
Wendouree Industrial Park
Ballarat Vic 3355
Freecall 1800 033 431
www.haymespaint.com.au